HIC HYDROPHOBIC INTERACTION CHROMATOGRAPHY

HIC PRODUCTS

TSKgel Ether-5PW
 TSKgel Phenyl-5PW
 TSKgel Butyl-5PW

= TOSOH FACT

Tosoh Bioscience provides solutions for today's biological purification needs. In fact, some of the first commercial HIC products were manufactured by Tosoh. We take pride in our ability to design new products based on existing chemistries to solve specific customer applications.

We encourage you to have a confidential discussion with us about your specific needs. Whether it is a surface modification of an existing product or the creation of a new one, we encourage you to call on us to meet your needs for a customized solution.



75



₽

INTRODUCTION TO TSK-GEL HIC COLUMNS

Hydrophobic Interaction Chromatography (HIC) is based on the interaction between hydrophobic groups on a protein and a hydrophobic ligand on the solid support. HIC offers a distinct advantage for easily denatured proteins; it can be run using moderate concentrations of ammonium sulfate, which favors the stability of many proteins.

The binding of proteins to a hydrophobic matrix is affected by a number of factors including (1) the type of ligand, (2) the ligand density on the solid support, (3) the backbone material of the matrix, (4) the hydrophobic nature of the protein, and (5) the type of salt used. All of these factors help to make HIC a powerful technique for the separation of biomolecules.

Tosoh Bioscience offers three different HIC column types in analytical format: TSKgel Phenyl-5PW, Ether-5PW and Butyl NPR. TSKgel Phenyl-5PW and Ether-5PW are also available in preparative column formats.

Column Selection

The HIC packing materials are based on the polymeric TSKgel G5000PW size exclusion resin (a hydrophilic gel with an estimated protein exclusion limit of 5,000,000 Da) which is then derivatized with oligoethylene-glycol (Ether-5PW) or phenyl (Phenyl-5PW) groups. Columns, depending on diameter, are packed with 10, 13 or 20 µm particles.

TSKgel Ether-5PW is less hydrophobic than TSKgel Phenyl-5PW. It displays weaker interaction and thus shorter retention times compared to Phenyl-5PW, as shown in FIGURE 1. TSKgel Ether-5PW is the best choice for the separation of very hydrophobic proteins such as membrane proteins or monoclonal antibodies.

The TSKgel Phenyl-5PW columns were the first commercially available, polymer-based columns for high performance HIC. These columns have been instrumental to the increase in popularity of this technique for analytical, preparative, and process scale separations of biopolymers. FIGURE 2 compares the separation of standard proteins on the Ether, Phenyl, and Butyl supports under similar operating conditions.

The base material of TSKgel Butyl-NPR is of the same chemical composition as the G5000PW base material used to prepare Phenyl-5PW and Ether-5PW. The difference between the two packings is that the G5000PW packing is porous, whereas the base material of the TSKgel Butyl-NPR column consists of spherical 2.5 μ m nonporous particles. Nonporous resins (NPR) are typically used for high-speed analytical applications. See FIGURE 3 for the structure of the HIC resins.

TSKgel Butyl-NPR is the least hydrophobic among the three TSK-GEL HIC columns and requires a higher salt concentration for binding. TSKgel Butyl-NPR columns provide fast and quantitative HIC, because smaller particles provide higher efficiency. By packing the 2.5 µm nonporous resin particles into shorter columns, typical analysis times are reduced to less than 10 minutes. Pore diffusion is often the rate-limiting step in the overall mass transport of large biomolecules through a porous column. Eliminating the pores provides higher resolution at higher flow rates. Another benefit of NPR resins is excellent mass recovery, allowing quantitation down to nanogram levels. These properties make TSKgel Butyl-NPR the preferred choice for process monitoring and quality control.

TSK-GEL HIC columns are compatible with water-soluble organic solvents at concentration below 50 % (20 % for Butyl-NPR).

- FEATURES
- Choice of three hydrophobic ligands (ether, phenyl or butyl)
- Rigid polymeric base resin
- Similar chemistry to Toyopearl resins
- TSKgel Phenyl-5PW offered in PEEK hardware
- Ether and Phenyl available in 2 mm ID format

- BENEFITS
- Added flexibility during method development
- Wide pH range (2-12) enabling robust cleaning options
- Seamless scalability from analytical to preparative scaley
- Eliminates undesirable interactions with column hardware
- LC-MS applications

Column selection for TSK-GEL HIC Columns

Sample	MW range (Da)	TSK-GEL Column
Peptides	< 10,000	Butyl-NPR
Medium to large proteins	> 10,000	Phenyl-5PW Ether-5PW Butyl-NPR
DNA, RNA, and PCR products	> 500,000	Phenyl-5PW Butyl-NPR
Oligonucleotides	> 10,000	Phenyl-5PW Butyl-NPR

FIGURE 1 _____

Separation of α -amylase



 Column:
 TSKgel Ether-5PW, 7.5mm ID x 7.5cm

 TSKgel Phenyl-5PW, 7.5mm ID x 7.5cm

 Sample:
 α-amylase

 Elution:
 A. 0.1mol/L phosphate buffer (pH 7.0) + 1.1mol/L Na₂SO₄

 B. 0.1mol/L phosphate buffer (pH 7.0)

 60min linear gradient from A→B(1.1mol/L→0mol/L Na₂SO₄)

 Flow Rate:
 1.0mL/min

 Detection:
 UV @ 280nm

FIGURE 3

Structure of TSK-GEL HIC resins



FIGURE 2

Comparing conventional and nonporous HIC columns



Sample capacity

One definition of sample capacity is the amount of pure compound injected onto the column at which the peak width is 10% larger than the peak width under low loading conditions. Using this definition, the capacity of a 7.5 mm ID x 7.5 cm L TSKgel Phenyl-5PW column varies from 0.1 to 1 mg of protein. Resolution and peak width are dependent on sample loading, as shown in FIGURE 4. Therefore, sample loading should be kept within 0.1-0.5 mg in order to obtain the highest resolution.

Separations on TSKgel Ether-5PW columns usually take 30-60 minutes. 0.5 mg of pure protein can be purified from a 5-10 mg crude protein mixture using a 7.5 mm ID x 7.5 cm L column.

Since almost all of the surface area of a porous particle is inside the pores, the capacity of the 4.6 mm ID x 3.5 cm L TSKgel Butyl-NPR column is significantly less than that for the 7.5 mm ID x 7.5 cm L Phenyl-5PW column. Capacities for the Butyl-NPR column are 100 μ g for crude sample and 2 μ g for pure sample.

HC



78

2

님

Chemical stability

TSK-GEL 5PW-type HIC columns are physically and chemically stable in water-soluble organic solvents (at < 50% methanol, ethanol, ACN, DMF, DMSO or < 30 % chloroform). Change the solvent gradually by reducing the flow rate (preferably with a gradient) because rapid change may cause degradation of column efficiency. Note: When changing to an organic solvent, reduce the salt concentration to prevent precipitation of the salt on the column. Also, chaotropic agents (urea, SDS, etc.) will reduce the adsorption of biomolecules; therefore, use low levels of these agents (<2 mol/L).

FIGURE 4

Dependence of peak width on sample loading in the separation of proteins



00101111					
Sample:	1. myoglobin; 2. ribonuclease A; 3. ovalbumin;				
	4. α -chymotrypsin; concentration: 0.025 % to 1.6 %				
Elution:	60 min linear gradient of (NH 4)2SO4 from 1.5 mol/L to				
	0 mol/L in 0.1 mol/L phosphate buffer (pH 7.0)				
Flow Rate:	0.5 mL/min				
Temperature:	25 °C				
Detection:	UV @ 280 nm				

TABLE 1

Long-term exposure of TSKgel Phenyl-5PW to acid and base

Acid/base	Phenyl content (mmol/mL - resin)			
	Before exposure	After 10 days exposure		
0.5 mol/L CH ₃ COOH	0.105	0.106		
0.5 mol/L NaOH	0.105	0.104		

The addition of organic solvents or chaotropic agents in the final buffer can improve separations. However, relative elution positions may change. Therefore, add chaotropic agent and organic solvent in small quantities. See FIGURE 5 for the effect of chaotropic agents and organic solvents on the HIC separation of two different samples.

Polymer-based columns are stable when cleaning at alkaline pH. All TSK-GEL HIC columns can be routinely operated from pH 2-12. Table I shows that the phenyl groups on the TSKgel Phenyl-5PW are stable for more than 10 days upon exposure to 0.5 mol/L NaOH or 0.5 mol/L acetic acid.

FIGURE 5

Effect of urea and isopropanol on the separation of commercial lipoxidase and a standard protein mixture



HIC

APPLICATIONS OF TSK-GEL ETHER-5PW COLUMNS

HIGHLIGHTS

- Ether, phenyl, and butyl functionalities are available.
- TSKgel Ether-5PW and Phenyl-5PW columns are available in a 2 mm ID format.
- Large 1000 Å pore size of the base matrix accommodates proteins up to 5 x 10⁶ Da.
- Polymeric resin is chemically and physically stable to changes in pH and ionic strength and compatible with a variety of organic solvents.
- High binding capacity is achieved for TSK-GEL 5PW-type HIC packing materials.
- Nonporous resins (NPR) allow fast analysis for guality control or process monitoring

Monoclonal Antibodies

Monoclonal antibodies (mAbs) play a part in many research, diagnostic, and therapeutic applications. Monoclonal antibodies are generally the most hydrophobic proteins in ascites fluid and cell culture supernatant. FIGURE 7 shows typical results from the screening of two mAbs.

Antibiotics

The TSKgel Ether-5PW column was used to determine the relative purity of the antibiotic components C-1027 and C-1027-AG as shown in FIGURE 8. Antibiotic C-1027 is composed of a

FIGURE 7 🚍 =

Screening of mouse monoclonal antibodies



Column: TSKgel Ether-5PW, 8.0mm ID x 7.5cm, glass A. 20 μ L unequilibrated mouse IgG_{2b} κ ascites Sample: B. 20μ L unequilibrated mouse IgM κ ascites Elution: linear gradient from Buffer A to B as shown Buffer A: 0.05mol/L sodium phosphate, pH 7.0, 2.0mol/L ammonium sulfate, 1.0mol/L glycine

Buffer B: 0.05mol/L sodium phosphate, pH 7.0, 1.0mol/L glyci Flow Rate: 1.0mL/min

Detection: UV @ 280nm

protein consisting of many hydrophobic and hydroxyamino acids with a non-protein chromophore. Antibiotic C-1027-AG is composed of the hydrophobic and hydroxyamino acids without the chromophore.

Human serum

FIGURE 9 displays the excellent recovery of albumin when 16 mL of human serum was purified on a 55 mm ID preparative TSKgel Ether-5PW column.



Purification of anti-tumor antibiotic



Elution:	linear gradient from 1.5mol/L to 0mol/L (NH ₄) ₂ SO ₄
	in 0.1mol/L phosphate buffer, pH 7.0
Flow Rate	0.8ml/min

UV @ 220nm Detection:

FIGURE 9

Human serum fractionated on preparative scale



Column:	TSKgel Ether-5PW, 55mm ID x 20cm				
Sample:	16mL human serum,1.2g total protein				
Elution:	36min linear gradient from 1.7mol/L to 0.68mol/L (NH,),SO,				
	followed by step gradient to $0 \text{mol/L} (\text{NH}_4)_2 \text{SO}_4 \text{ in } 0.1 \text{mol/L}$				
	phosphate buffer, pH 7.0				
Flow Rate:	40mL/min				
Detection:	UV @ 280nm				
Recovery:	92% of the albumin was recovered in the fraction indicated by the vertical lines				

≌



80

일

APPLICATIONS OF TSK-GEL PHENYL-5PW COLUMNS

Recovery of biological activity for milligram to sub-gram amounts of enzymes eluted from TSKgel Phenyl-5PW columns is shown in the table below. In all cases, at least 80 % of the enzymatic activity was recovered.

TABLE II =

Recovery of enzymatic activity from TSKgel Phenyl-5PW at various loadings

Enzyme	Recovery (%)
lpha-Chymotrypsin, 0.4 mg	92
β -Amylase, 1.3 mg	80
Ferredoxin NADP reductase, 3.0 mg	100
Lactate dehydrogenase, 54 mg	93
Lipoxidase, 1.0 mg	89
Lipoxidase, 200 mg	86
Lysozyme, 0.05 mg	90
Lysozyme, 0.2 mg	90
Phosphoglucose isomerase, 100 mg	96

RNAs

FIGURE 10 illustrates the separation of 16S and 23S ribosomal RNA on a TSKgel Phenyl-5PW column. The approximate molecular weights of these RNAs are 560,000 and 1,100,000 Da, respectively.

Proteins

FIGURE 11 compares the resolution of standard proteins on analytical and preparative TSKgel Phenyl-5PW columns. Different flow rates compensated for the change in particle size and column dimensions. High resolution was obtained on both columns.

FIGURE 10 -----Ξ

Retain large RNAs on TSKgel Phenyl-5PW



Scale up to preparative separations

FIGURE 11



Column:	TSKgel Phenyl-5PW, A.) 7.5mm ID x 7.5cm and
Sample:	B.) 21.5mm ID x 15cm 1. myoglobin, 2. ribonuclease A, 3. lysozyme,
	4. α -chymotrypsinogen, 5. α -chymotrypsin
Elution:	60min linear gradient from 1.8mol/L to 0mol/L (NH ₄) ₂ SO ₄
	in 0.1mol/L phosphate buffer, pH 7.0
Flow Rate:	0.5mL/min (7.5mm ID) or 4mL/min (21.5mm ID)
Detection:	UV @ 280nm

HIC

APPLICATIONS OF TSK-GEL BUTYL-NPR COLUMNS

Proteins

Although loading capacity is limited on NPR columns, small scale separation of proteins is possible.

Almost identical separations were obtained at sample loads from 25 μ g up to 100 μ g in the separation of a crude sample of phosphoglucose isomerase as shown in FIGURE 12.

FIGURE 13 shows the separation of Fab and Fc fragments of an antibody on TSKgel Butyl-NPR. The appearance of additional Fc fragments is due to the oxidation of methionine residues by 0.10% t-butylhydroperoxide (tBHP). The numbers above the Fc peaks correspond to the number of oxidized residues in each fragment.

Visit our website:

www.tosohbioscience.com for additional applications, product specifications and literature.

Contact our Technical Service specialists to discuss your specific application: +49 (0)711 13257-0 or techsupport.sep@ tosoh.com.

Please see next page for ordering information.

FIGURE 13

■ FIGURE 12

Effect of sample load on the separation of phosphoglucose isomerase



Column:	TSKgel Butyl-NPR, 4.6mm ID x 3.5cm				
Sample:	crude sample of phosphoglucose isomerase				
Loads:	А. 25µg; В. 100µg				
Elution:	10min linear gradient of (NH ₄) ₂ SO ₄ from 1.8mol/L				
	to Omol/L in 0.1mol/L phosphate buffer, pH 7.0				
Flow Rate:	1.0mL/min				
Temperature:	25°C				
Detection:	UV @ 280nm				

Separation of F_{ab} and F_c fragments on TSKgel Butyl-NPR



Column:	TSKgel Butyl-NPR, 4.6mm ID x 3.5cm
Elution:	Buffer A: 2mol/L (NH ₄) ₂ SO ₄ , 20mmol/L Tris, pH7
	Buffer B: 20mmol/L Tris, pH7
Gradient:	linear from 10%B to 100%B in 34 minutes
Flow rate:	1mL/min
Temperature:	30°C

81

HC



ORDERING INFORMATION

Part #	Description	ID	Length	Particle	Number	Flow Rate (mL/min)		Maximum
		(mm)	(cm)	Size (µm)	Theoretical	Range	Max	Pressure
Glass	columns				Fidles			Drop (kg/cm²)
14013	Ether-5PW Glass, 1000 Å	5.0	5.0	10.0	≥ 600	0.5 - 0.8	1.0	20
14014	Ether-5PW Glass, 1000 Å	8.0	7.5	10.0	≥ 1,000	0.5 - 1.0	1.2	20
14015	Ether-5PW Glass, 1000 Å	20.0	15.0	13.0	≥ 3,000	4.0 - 6.0	8.0	20
13063	Phenyl-5PW Glass, 1000 Å	5.0	5.0	10.0	≥ 600	0.5 - 0.8	1.0	20
08804	Phenyl-5PW Glass, 1000 Å	8.0	7.5	10.0	≥ 1,000	0.5 - 1.0	1.2	20
14018	Phenyl-5PW Glass, 1000 Å	20.0	15.0	13.0	≥ 3,000	4.0 - 6.0	8.0	20
Stainle	ess steel columns							
18760	Ether-5PW, 1000 Å	2.0	7.5	10.0	≥ 1,000	0.05 - 0.10	0.12	6
08641	Ether-5PW, 1000 Å	7.5	7.5	10.0	≥ 1,000	0.5 - 1.0	1.2	20
08642	Ether-5PW, 1000 Å	21.5	15.0	13.0	≥ 3,000	4.0 - 6.0	8.0	20
16255	Ether-5PW, 1000 Å	55.0	20.0	20.0	≥ 1,500	20.0 - 30.0	40.0	5
18759	Phenyl-5PW, 1000 Å	2.0	7.5	10.0	≥ 1,000	0.05 - 0.10	0.12	8
07573	Phenyl-5PW, 1000 Å	7.5	7.5	10.0	≥ 1,000	0.5 - 1.0	1.2	20
07656	Phenyl-5PW, 1000 Å	21.5	15.0	13.0	≥ 3,000	4.0 - 6.0	8.0	20
07938	Phenyl-5PW, 1000 Å	55.0	20.0	20.0	≥ 1,500	20.0 - 40.0	50.0	4
14947	Butyl-NPR, nonporous	4.6	3.5	2.5		0.5 - 1.0	1.2	200
PEEK o	columns							
20023	BioAssist Phenyl, 1000 Å	7.8	5	10.0	≥ 1,000	0.5 - 1.0	1.2	20
Guard	column products		ID	Length	Particle			
			(mm)	(cm)	Size (µm)			
42156	Ether-5PW Guard cartridge	!	2.0	1.0	10.0	For P/N 18760		
14025	Ether-5PW Guardgel Kit, Gl	ass			20.0	For P/Ns 14013	and 14014	
08643	B Ether-5PW Guardgel Kit				20.0	For P/N 08641		
16091	Ether-5PW Prep Guardgel I	Kit			20.0	For P/N 08642		
14470	Ether-5PW Guard column, Glass		20.0	2.0	13.0	For P/N 14015		
16253	Ether-5PW Guard column		45.0	5.0	20.0	For P/N 16255		
42155	5 Phenyl-5PW Guard cartridge		2.0	1.0	10.0	For P/N 18759		
80880	8 Phenyl-5PW Guardgel Kit, Glass				20.0	For P/Ns 08804	and 13063	
07652	i2 Phenyl-5PW Guardgel Kit				20.0	For P/N 07573		
16095	95 Phenyl-5PW Prep Guardgel Kit				20.0	For P/N 07656		
14469	1469 Phenyl-5PW Guard column, Glass		20.0	2.0	13.0	For P/N 14018		
07936	36 Phenyl-5PW Guard column		45.0	5.0	20.0	For P/N 07938		
19308	08 Guard cartridge holder		2.0	1.5		For all 2 mm ID	Guard cartridges	

82

HIC